

Water Purifier EQ2 Installation Manual



Product description

Model/Name	EQ2
Filter type	Quick-change filter
Machine size	20(L)*10(W)*32(H)cm
Flow rate	1.5LPM
1st stage S2-05 5 micron PP filter (lifespan: 3 months)	
Function	To remove sand, silt, dirt and rust and other impurities down to nominal size of 5 micron.
2nd stage S2-CTO 5 micron Carbon Block filter (lifespan: 6 months)	
Function	To remove volatile organic chemicals, chlorine and many other harmful chemicals.
Accessories	70PSI dual CV PLV manual PE tube Feed water connector with ball valve Connector

How to install

1. Remove the water purifier from the box, together with the accessories of tubing, clips and valve.
2. Access the location to place this water purifier, water dispenser, or drinking tap with advice and input from the homeowners
3. Take measurements and drill holes (optional) in the carpentry of the cabinets to hold the brackets of the water purifier.
4. Attach the water purifier to dispense filtered water directly from the current faucet or directed from a new faucet and/or a dispenser.
5. Connect the water tubing to the water mains.
6. Connect the water tubing to the drinking faucet.
7. Allow the flushing by dispensing the water for about 20 minutes until water is clear.
8. The presence of water bubbles is normal and will soon disappear.

Water Purifier EQ2 Installation Manual

Support & General Maintenance

- ◆ Cleaning Instructions Dispenser:

Use a damp cloth to wipe the surfaces – Do not use cleaning agents that may cause discolouration and corrosion to the plated surfaces.

- ◆ Troubleshooting

Leakage:

In the unlikely event of leakage, turn off the water valve supplying water to the modules and contact our Technical Support.

- ◆ Recommendations:

If water filtration unit is left unused for more than 2 days due to e.g. overseas travels, office closure etc., we highly recommend the following:

- Turn off the water inlet valve supplying water to the filtration
- When turning it back on for use, flush out the stagnant water within the system by turning on the tap for at least 2 minutes before consumption

Do not store hazardous chemical by-products such as cleaning agents and pesticides near the filtration system, to prevent any possible contamination.

- ◆ Installation shall be in accordance with AS/NZS 3500.1.